


# Technical Data Sheet

MAY 2017, REV:02

## MELFLEX<sup>®</sup> DOTP-H

(Bis (2-ethylhexyl) Terephthalate)

**CAS NUMBER:** 6422-86-2  
**EINECS NUMBER:** 229-176-9  
**REACH REF. NUMBER:** 01-2119446265-39-0007  
**MOLECULAR FORMULA:** C<sub>24</sub>H<sub>38</sub>O<sub>4</sub>  
**MOLECULAR WEIGHT:** 390.57



PARAMETERS	VALUE	METHODS
ESTER %	> 99,00	ASTM D3465
REFRACTIVE INDEX (Typical Value)	1,4895	ASTM D1045-08(D1218)
SPECIFIC GRAVITY 20/20°C (g/cm <sup>3</sup> )	0,995 ± 0,015	ASTM D1045-08(D287-D4052)
VISCOSITY (cP) 20°C	115 ± 35	BROOKFIELD METHOD
ACIDITY( as mgKOH/g ) (%)	2,5 Max.	ASTM D1045-08
WATER CONTENT (Karl Fischer) %	0,05 Max.	ASTM D1045-08(E203)
OPEN CUP FLASH POINT(COC),°C	> 190	ASTM D-92
VOLALITE SUBSTANCE (3 hours at 125°C) %	0,6 Max.	ILL 003/1-04-48
APPEARANCE	Clear and Amber colour	VISUAL EXAMINATION

### Applications:

Films, sheets, table cloths, conveyor belts, artificial leathers, wall coverings, strips, profiles, shingles, wires, cables, shoe soles, sealants, shades



PET Resin, Plasticers & PVC FloorCover

**Address:** Batı Otoban Bağlantı Yolu Üzeri Büyük Dikili Mah.93099 Sok.No: 4/A Seyhan/ADANA/TURKEY  
Tel:+90-322 485 62 67 Fax:+90-322 485 62 03

[www.meltemkimya.com.tr](http://www.meltemkimya.com.tr)

**Operating With:** ISO 9001-2000, ISO 14001, OHSAS 18001-2004, TSE